

## Agricultural Marketing Service, USDA

## § 58.517

dry storage space in which any raw material, packaging or ingredients supplies or finished products are handled, processed, packaged or stored shall be designed and constructed to assure clean and orderly operations.

(b) *Ventilation.* Processing and packaging rooms or compartments shall be ventilated to maintain sanitary conditions, preclude the growth of mold and air borne bacterial contaminants, prevent undue condensation of water vapor and minimize or eliminate objectionable odors. To minimize air borne contamination in processing and packaging rooms a filtered air supply meeting the requirements of § 58.510(c) shall be provided. The incoming air shall exert an outward pressure so that the movement of air will be outward and prevent the movement of unfiltered air inward.

(c) *Starter facility.* A separate starter room or properly designed starter tanks and satisfactory air movement techniques shall be provided for the propagation and handling of starter cultures. All necessary precautions shall be taken to prevent contamination of the room, equipment and the air therein. A filtered air supply with a minimum average efficiency of 90% when tested in accordance with the ASHRAE Synthetic Dust Arrestance Test should be provided so as to obtain an outward movement of air from the room to minimize contamination.

(d) *Coolers.* Coolers shall be equipped with facilities for maintaining proper temperature and humidity conditions, consistent with good commercial practices for the applicable product, to protect the quality and condition of the products. Coolers shall be kept clean, orderly and free from mold, and maintained in good repair. They shall be adequately lighted and proper circulation of air shall be maintained at all times. The floors, walls, and ceilings shall be of such construction as to permit thorough cleaning.

### EQUIPMENT AND UTENSILS

#### § 58.511 General construction, repair and installation.

The equipment and utensils used for the manufacture and handling of cottage cheese shall be as specified in

§ 58.128. In addition for certain other equipment the following requirements shall be met.

#### § 58.512 Cheese vats or tanks.

(a) Cheese vats or tanks shall meet the requirements of § 58.416. When direct steam injection is used for heating the milk, the vat or tank may be of single shell construction. The steam shall be culinary steam.

(b) Vats shall be equipped with valves to control the heating and cooling medium and a suitable sanitary outlet valve. Vats used for creaming curd should be equipped with a refrigerated cooling medium. A circulating pump for the heating and cooling medium is recommended.

#### § 58.513 Agitators.

Mechanical agitators shall meet the requirements of § 58.417.

#### § 58.514 Container fillers.

Shall comply with the 3-A Sanitary Standards for Equipment for Packaging Frozen Desserts and Cottage Cheese.

#### § 58.515 Mixers.

Only mixers shall be used which will mix the cheese carefully and keep shattering of the curd particles to a minimum. They shall be constructed in such a manner as to be readily cleanable. If shafts extend through the wall of the tank below the level of the product, they shall be equipped with proper seals which are readily removable for cleaning and sanitizing. The mixer shall be enclosed or equipped with tight fitting covers.

#### § 58.516 Starter vats.

Bulk starter vats shall meet the requirements of § 58.415.

### QUALITY SPECIFICATIONS FOR RAW MATERIAL

#### § 58.517 General.

Raw materials used for manufacturing cottage cheese shall meet the following quality specifications.